Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer care, Østergade, Copenhagen, DK

Model identifier: Ambit Pendant 16.5

7/10 01 11/2011						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Gx53 - 220-240V					
(or other electric interface)	~ 50/60Hz					
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						

		1 Todact parar					
Parameter		Value	Parameter	Value			
General product parameters:							
0,	nption in on- 00 h), rounded st integer	6	Energy efficiency class	G			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	316 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode pow pressed in W	ver (P _{on}), ex-	6,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90			
Outer dimen-	Height	98	Spectral power dis-	See image			
sions without	Width	165	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	165	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,467			
		nates (x and y)	0,415			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	64	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,92	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,0			

(a)'-': not applicable; (b)'-': not applicable;

